

PERFORMANCE DATA SHEET

PARAGON WATER SYSTEMS, INC.
14001 – 63RD Way N., Clearwater, FL 33760

800.288.9708

Shower Filter Model: P-WMF-1
Replacement Cartridge Model: SFRC

SPECIFICATIONS and OPERATIONAL LIMITS

Rated Service Flow	2.0 gpm (7.5 lpm)
Capacity	10,000 gallons (38,000 liters)
Operating Pressure Range	40-100 psi (280-690 kPa)
Operating Temperature Range	40° - 120°F (4° - 49°C)

This system has been tested according to NSF/ANSI 177 for reduction of free available chlorine. The concentration of free available chlorine in water entering the system was reduced to a concentration less than or equal to the permissible limit for water leaving the system, as specified in NSF/ANSI 177.

PARAMETER	INFLUENT CHALLENGE	MINIMUM CHLORINE REDUCTION	ACTUAL CHLORINE REDUCTION
FREE AVAILABLE CHLORINE	2 mg/L FAC	≥ 50 % FAC	96% FAC

Testing was performed under standard laboratory conditions; actual performance may vary.

WARNING: Filter cartridge must be replaced at least once per year. Failure to replace this unit may result in the deterioration and instability of the showerhead.

LIMITED WARRANTY

Paragon Water Systems warrants to the owner of the product, for a period of 90 days from the date of purchase, that it is free from defects in material and workmanship and agrees that it will, at its' option, either repair the defect or replace the defective product or part thereof at no charge to the purchase for parts or labor.

If within 90 days from the date of purchase, the product proves to be defective for any reason, return it postpaid to Paragon Water Systems at the address below for repair or replacement at no charge.

This warranty does not apply to any product the exterior of which has been damaged or defaced, which has been subjected to commercial usage, misuse, abnormal service or maintenance neglect, or which has been altered or modified in design or construction.

The buyer and/or user accept all responsibility and liability for the use of this product. Paragon Water's responsibility is limited to the repair or replacement of defective merchandise that fails within the specified warranty period. Paragon Water's liability for special, incidental or consequential damages is expressly disclaimed.

PARAGON WATER SYSTEMS, INC.
14001 – 63rd Way N.
Clearwater, FL 33760

INSTALLATION INSTRUCTIONS FOR THE CLEAN & PURE® SHOWER SPA WALL MOUNT MODEL WMF-1

Installation Instructions

1. Remove existing showerhead from shower.
2. Wrap Teflon® tape tightly around shower pipe threads.



3. Place your new filter on shower pipe.
Use a soft cloth to protect the finish and tighten by hand.
4. Check system for leaks and tighten as appropriate.



Cartridge Replacement Instructions

1. Hold body of showerhead firmly in one hand. With the other hand, turn the ribbed ring behind face counter-clockwise to unscrew.
2. Grasp white filter cartridge, pull filter up and to the side to remove. Replace new filter by pushing it firmly down into the cavity until seated.
3. Align threads by turning whole faceplate counter-clockwise until faceplate clicks into cavity.
4. Turn only the ribbed ring behind faceplate in a clockwise direction until secure.

